

# AGRIMAX RT 657



AGRIMAX RT 657 is the ideal tire for soil tillage and on-the-road usage; some sizes are also suitable for vineyard harvesting. This tire guarantees an excellent driving comfort as well as significant fuel savings. Agrimax RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

## MACHINERY

### AGRICULTURE

TRACTOR - VINEYARD HARVESTER

## APPLICATIONS

### AGRICULTURE

FIELD AND ROAD TRANSPORT - SOIL TILLAGE  
VINEYARD HARVESTING

## PLUS



COMFORT



HANDLING



FUEL ECONOMY



HIGH LOAD CAPACITY



TRACTION



REDUCED SOIL  
COMPACTION



HIGH SPEED

# PRODUCT: AGRIMAX RT 657



## TECHNICAL DATA U/M: INTERNATIONAL STANDARD (MM)

Size	LI/SS	RIM REC	SW	OD	SLR	RC	Type	TRA Code
320/65 R 16	117 D/120 A8	W 10	319	822	366	2466	TL	
320/65 R 18	109 A8/B	W 10	319	873	392	2587	TL	
340/65 R 18	113 A8/B	W 11	343	899	400	2667	TL	
340/65 R 20	124 D/127 A8	W 11	343	950	430	2892	TL	
420/65 R 20	135 D/138 A8	W 13	418	1054	468	3162	TL	
440/65 R 20	138 D/141 A8	W 14 L	441	1080	479	3240	TL	
420/65 R 24	138 D/141 A8	W 13	418	1156	519	3468	TL	R-1W
440/65 R 24	135 D/138 A8	W 14 L	441	1182	538	3546	TL	R-1W
480/65 R 24	140 D/143 A8	W 15 L	479	1234	562	3730	TL	R-1W
540/65 R 24	146 D/149 A8	W 16 L	530	1312	590	3930	TL	R-1W
420/65 R 28	135 D/138 A8	W 13	418	1257	584	3824	TL	
440/65 R 28	138 D/141 A8	W 14 L	441	1283	590	3878	TL	R-1W
480/65 R 28	142 D/145 A8	W 15 L	479	1335	610	4058	TL	R-1W
540/65 R 28	149 D/152 A8	W 16 L	530	1413	643	4253	TL	R-1W
600/65 R 28	154 D/157 A8	DW 20 B	611	1491	670	4470	TL	R-1W
420/65 R 30	136 D/139 A8	W 13	418	1308	606	3952	TL	
540/65 R 30	150 D/153 A8	W 16 L	530	1464	670	4403	TL	R-1W
600/65 R 30	155 D/158 A8	DW 20 B	611	1542	697	4609	TL	R-1W
540/65 R 34	152 D/155 A8	W 16 L	530	1566	712	4742	TL	R-1W
600/65 R 34	157 D/160 A8	DW 20 B	611	1644	742	4960	TL	R-1W
540/65 R 38	153 D/156 A8	W 16 L	530	1667	760	5059	TL	R-1W
600/65 R 38	159 D/162 A8	DW 20 B	611	1745	790	5247	TL	R-1W
650/65 R 38	163 D/166 A8	DW 20 B	645	1811	830	5483	TL	R-1W
650/65 R 42	165 D/168 A8	DW 20 B	645	1913	878	5824	TL	R-1W