

AGRIMAX RT 765



AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction on all surfaces at any time.

MACHINERY

AGRICULTURE

SPRAYER - TRACTOR - VINEYARD HARVESTER

APPLICATIONS

AGRICULTURE

FIELD AND ROAD TRANSPORT - SOIL TILLAGE -
SPRAYING VINEYARD HARVESTING

PLUS



COMFORT



TRACTION



SELF CLEANING



REDUCED SOIL
COMPACTION

PRODUCT: AGRIMAX RT 765



TECHNICAL DATA U/M: INTERNATIONAL STANDARD (MM)

Size	Version	LI/SS	RIM REC	SW	OD	SLR	RC	Type	TRA Code
200/70 R 16		94 A8/B	W 6	197	686	313	2058	TL	
220/70 R 16		99 A8/B	W7	221	715	324	2145	TL	
240/70 R 16		104 A8/B	W 8	244	742	335	2226	TL	
260/70 R 16		109 A8/B	W 8	258	770	346	2310	TL	
280/70 R 16		112 A8/B	W 9	282	798	356	2370	TL	
280/70 R 18		114 A8/B	W 9	282	849	381	2520	TL	
260/70 R 20		113 A8/B	W 8	258	872	402	2639	TL	
280/70 R 20		116 A8/B	W 9	282	900	408	2705	TL	
300/70 R 20		120 A8/B	W 9	295	952	428	2854	TL	
320/70 R 20		123 A8/B	W 10	319	982	445	2965	TL	
360/70 R 20		129 A8/B	W 11	357	1042	469	3122	TL	
380/70 R 20		132 A8/B	W 12	380	1082	482	3213	TL	
320/70 R 24		116 A8/B	W 10	319	1094	502	3245	TL	R-1W
360/70 R 24		122 A8/B	W 11	357	1152	519	3400	TL	R-1W
380/70 R 24		125 A8/B	W 12	380	1190	538	3560	TL	R-1W
420/70 R 24		130 A8/B	W 13	418	1248	554	3680	TL	R-1W
480/70 R 24		138 A8/B	W 15 L	479	1316	580	3894	TL	R-1W
360/70 R 28		125 A8/B	W 11	357	1251	579	3767	TL	R-1W
380/70 R 28		127 A8/B	W 12	380	1293	586	3883	TL	R-1W
420/70 R 28		133 A8/B	W 13	418	1349	604	4020	TL	R-1W
480/70 R 28		140 A8/B	W 15 L	479	1421	634	4183	TL	R-1W
420/70 R 30		134 A8/B	W 13	418	1398	631	4172	TL	R-1W
480/70 R 30		141 A8/B	W 15 L	479	1478	659	4322	TL	R-1W
600/70 R 30		152 A8/B	DW 20 B	591	1602	711	4774	TL	R-1W
480/70 R 34		149 A8/B	W 15 L	479	1580	711	4759	TL	R-1W
480/70 R 34		155 A8/B	W 15 L	479	1580	711	4759	TL	R-1W
520/70 R 34		148 A8/B	W 16 L	516	1640	739	4901	TL	R-1W
480/70 R 38		145 A8/B	W 15 L	479	1681	764	5015	TL	R-1W
520/70 R 38		150 A8/B	W 16 L	516	1749	793	5300	TL	R-1W
580/70 R 38		155 A8/B	W 18 L	577	1827	821	5505	TL	R-1W
580/70 R 38	STEEL BELTED	180 A8	W 18 L	577	1827	821	5505	TL	R-1W
620/70 R 38		170 A8/B	DW 20 B	625	1833	828	5591	TL	R-1W
710/70 R 38		166 A8/B	DW 23 B	716	1959	859	5751	TL	R-1W
710/70 R 38		171 D/174 A8	DW 23 B	716	1959	859	5751	TL	R-1W
710/70 R 38		178 A8/B	DW 23 B	716	1959	859	5751	TL	R-1W
620/70 R 42		160 A8/B	DW 20 B	625	1935	876	5742	TL	R-1W
620/70 R 42		166 A8/B	DW 20 B	625	1935	876	5742	TL	R-1W
710/70 R 42		173 A8/B	DW 23 B	716	2061	922	6174	TL	R-1W
710/70 R 42		173 D/176 A8	DW 23 B	716	2061	922	6174	TL	R-1W
620/70 R 46		162 A8/B	DW 20 B	625	2036	906	6047	TL	R-1W