

AGRIMAX RT 855



AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

MACHINERY

AGRICULTURE

SPRAYER - TRACTOR - VINEYARD HARVESTER

APPLICATIONS

AGRICULTURE

FIELD AND ROAD TRANSPORT - SOIL TILLAGE -
SPRAYING VINEYARD HARVESTING

PLUS



TRACTION



SELF CLEANING



DURABILITY



COMFORT

PRODUCT: AGRIMAX RT 855



TECHNICAL DATA U/M: INTERNATIONAL STANDARD (MM)

Size	Version	LI/SS	RIM REC	SW	OD	SLR	RC	Type	TRA Code
180/95 R 16		105 A8/B	5.5 F	185	760	340	2265	TL	
210/95 R 16		106 A8/B	W 7	214	806	360	2415	TL	
210/95 R 18		108 A8/B	W 7	214	855	385	2565	TL	
210/90 R 20		110 A8/B	W 7	211	890	412	2681	TL	
210/95 R 20		110 A8/B	W 7	214	908	418	2749	TL	
250/85 R 20		116 A8/B	W 8	250	940	424	2812	TL	
280/85 R 20		112 A8/B	W 10	292	984	441	2952	TL	
320/85 R 20		119 A8/B	W 11	329	1052	467	3100	TL	
250/85 R 22		113 A8/B	W 8	251	985	453	2964	TL	R-1W
250/85 R 24		109 A8/B	W 8	251	1036	475	3104	TL	R-1W
280/85 R 24		115 A8/B	W 10	292	1086	492	3224	TL	R-1W
320/85 R 24		122 A8/B	W 11	329	1154	518	3424	TL	R-1W
340/85 R 24		125 A8/B	W 12	353	1188	531	3540	TL	R-1W
380/85 R 24		131 A8/B	W 12	380	1256	554	3699	TL	R-1W
420/85 R 24		137 A8/B	W 15 L	438	1324	582	3900	TL	R-1W
250/85 R 28		112 A8/B	W 8	251	1137	519	3421	TL	R-1W
280/85 R 28		118 A8/B	W 10	292	1187	545	3558	TL	R-1W
320/85 R 28		124 A8/B	W 11	329	1255	569	3743	TL	R-1W
340/85 R 28		127 A8/B	W 12	353	1289	588	3890	TL	R-1W
380/85 R 28		133 A8/B	W 12	380	1357	606	4015	TL	R-1W
420/85 R 28		139 A8/B	W 15 L	438	1425	638	4214	TL	R-1W
380/85 R 30		135 A8/B	W 12	380	1408	633	4169	TL	R-1W
420/85 R 30		140 A8/B	W 15 L	438	1475	661	4393	TL	R-1W
460/85 R 30		145 A8/B	W 16 L	475	1544	682	4537	TL	R-1W
320/85 R 32		126 A8/B	W 11	329	1357	621	4081	TL	R-1W
320/85 R 34		141 A8/B	W 11	329	1408	645	4280	TL	R-1W
380/85 R 34		137 A8/B	W 12	380	1509	682	4504	TL	R-1W
420/85 R 34		142 A8/B	W 15 L	438	1578	709	4677	TL	R-1W
460/85 R 34		147 A8/B	W 16 L	475	1646	721	4865	TL	R-1W
320/85 R 36		128 A8/B	W 11	329	1458	672	4404	TL	R-1W
340/85 R 36		132 A8/B	W 12	353	1492	689	4507	TL	R-1W
320/85 R 38		143 A8/B	W 10	319	1509	700	4580	TL	R-1W
340/85 R 38		133 A8/B	W 12	353	1543	712	4613	TL	R-1W
380/85 R 38		139 A8/B	W 12	380	1611	736	4841	TL	R-1W
420/85 R 38		144 A8/B	W 15 L	438	1679	763	4992	TL	R-1W
460/85 R 38		149 A8/B	W 16 L	475	1747	785	5161	TL	R-1W
480/80 R 38		149 A8/B	W 16 L	475	1747	785	5161	TL	R-1W
520/85 R 38		155 A8/B	DW 16 L	516	1849	813	5393	TL	R-1W
520/85 R 38		170 A8/B	DW 16 L	516	1849	813	5393	TL	R-1W
480/80 R 42		151 A8/B	W 16 A ; DD 16 ; DW 16 A	479	1835	835	5459	TL	R-1W
520/85 R 42		157 A8/B	DW 16 A ; W 16 A ; DD 16	516	1951	858	5735	TL	R-1W
520/85 R 42		167 A8/B	DW 16 A ; W 16 A ; DD 16	516	1951	858	5735	TL	R-1W
420/80 R 46		151 D/162 A2	W 13	418	1840	863	5619	TL	R-1W
420/80 R 46		159 D/170 A2	W 13	418	1840	863	5619	TL	R-1W
480/80 R 46		158 A8/B	DW 16 A ; W 16 A ; DD 16	479	1936	895	5871	TL	R-1W

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints.

All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..

PRODUCT: AGRIMAX RT 855



TECHNICAL DATA U/M: INTERNATIONAL STANDARD (MM)

Size	Version	LI/SS	RIM REC	SW	OD	SLR	RC	Type	TRA Code	
480/80 R 46		164 A8/B	DW 16 A ; W 16 A ; DD 16	479	1936	895	5871	TL	R-1W	
520/85 R 46		158 A8/B	DW 16 L ; W 16 A ; W 16 L ; DD 16	516	2052	949	6252	TL	R-1W	
520/85 R 46		173 A8/B	DW 16 L ; W 16 A ; W 16 L ; DD 16	516	2052	949	6252	TL	R-1W	
480/80 R 50		159 A8/B	DW 16 A	489	2036	941	6158	TL	R-1W	
480/80 R 50	STEEL BELTED	176 A8	DW 16 A	489	2036	945	6228	TL	R-1W	