

AGRIMAX RT 955



AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying. The special tread design with a rounded shoulder provides excellent traction performance and continuous contact on the land in order to protect both valuable crops and soil from damage.

MACHINERY

AGRICULTURE

SPRAYER - TRACTOR - VINEYARD HARVESTER

APPLICATIONS

AGRICULTURE

ROW CROPS - SPRAYING - VINEYARD HARVESTING

PLUS



TRACTION



SELF CLEANING



STABILITY



DURABILITY



FIELD PROTECTION

PRODUCT: AGRIMAX RT 955



TECHNICAL DATA U/M: INTERNATIONAL STANDARD (MM)

Size	Version	LI/SS	RIM REC	SW	OD	SLR	RC	Type	TRA Code
210/90 R 24		107 A8/B	W 7	214	1010	462	3027	TL	R-1
210/95 R 28		116 A8/B	W 7	214	1111	513	3333	TL	R-1
210/95 R 32		120 A8/B	W 7	214	1213	571	3703	TL	R-1
230/95 R 32		128 A8/B	W 8	238	1251	585	3792	TL	R-1
270/95 R 32		136 A8/B	W 9	275	1327	614	4044	TL	R-1
230/95 R 36		130 A8/B	W 8	238	1352	639	4112	TL	R-1
270/95 R 36		139 A8/B	W 9	275	1428	665	4368	TL	R-1
270/95 R 38		140 A8/B	W 9	275	1479	697	4510	TL	R-1
230/95 R 40		132 A8/B	W 7	228	1454	690	4445	TL	R-1
230/95 R 42		133 A8/B	W 8	238	1506	714	4633	TL	R-1
300/85 R 42		144 A8/B	W 9	295	1577	745	4850	TL	R-1
210/95 R 44		120 A8/B	W 7	214	1518	716	4554	TL	R-1
230/95 R 44		134 A8/B	W 8	238	1556	739	4788	TL	R-1
270/95 R 44		142 A8/B	W 9	275	1632	764	4983	TL	R-1
270/95 R 46		143 A8/B	W 9	275	1683	786	5049	TL	R-1
300/95 R 46		148 A8/B	W 9	295	1738	812	5318	TL	R-1
300/95 R 46	SPECIAL	148 A8/B	W 9	295	1738	812	5318	TL	R-1
340/85 R 46		150 A8/B	W 12	353	1746	811	5238	TL	R-1
230/95 R 48		136 A8/B	W 8	238	1656	792	5085	TL	R-1
270/95 R 48		144 A8/B	W 9	275	1733	820	5351	TL	R-1
340/85 R 48		152 A8/B	W 12	353	1797	855	5572	TL	R-1
300/95 R 52		151 A8/B	W 9	295	1891	889	5822	TL	R-1
270/95 R 54		146 A8/B	W 9	275	1885	878	5815	TL	R-1