



AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

MACHINERY

AGRICULTURE

HAY HARVESTER / BALER - IMPLEMENT MACHINERY -
SMALL TRACTOR - TRAILER

INDUSTRIAL

TELEHANDLER - TRAILER

APPLICATIONS

AGRICULTURE

HAULAGE - HAY HARVESTING - LOADING - SOIL
TILLAGE

INDUSTRIAL

HAULAGE -

PLUS



AGRO-INDUSTRIAL USE



SUITABLE FOR LOOSE
SURFACE



TRACTION



SELF CLEANING

PRODUCT: AS 504



TECHNICAL DATA U/M: INTERNATIONAL STANDARD (MM)

Size	Version	LI/SS	PR	RIM REC	SW	OD	SLR	RC	Type
6.5/80 - 12			4	5 J	163	588	273	1851	TT
6.5/80 - 12			4	5 J	163	588	273	1851	TL
6.5/80 - 12			6	5 J	163	588	273	1851	TT
6.5/80 - 12			6	5 J	163	588	273	1851	TL
6.5/80 - 12	HD		6	5 J	163	588	273	1851	TT
7.00 - 12			4	4.5	187	683	300	2001	TT
7.00 - 12			4	4.5	187	683	300	2001	TL
7.00 - 12			6	4.5	187	683	300	2001	TL
7.00 - 12	ARAMID BELTED		8	4.5	187	683	300	2001	TL
7.00 - 12	SPECIAL		8	4.5	187	683	300	2001	TL
11.0/65 - 12			8	9.00	273	700	321	2072	TT
11.0/65 - 12			8	9.00	273	700	321	2072	TL
5.00 - 15			4	3.50 D	140	657	308	1957	TT
5.00 - 15			6	3.50 D	140	657	308	1957	TT
5.00 - 15			6	3.50 D	140	657	308	1957	TL
7.5L - 15			6	6 LB	210	765	354	2280	TT
7.5L - 15			8	6 LB	210	765	354	2280	TT
7.5L - 15			8	6 LB	210	765	354	2280	TL
7.5L - 15	ARAMID BELTED HD		8	6 LB	210	765	354	2280	TL
7.5L - 15	HD		8	6 LB	210	765	354	2280	TT
10.0/75 - 15.3			8	9.00	264	780	345	2285	TT
10.0/75 - 15.3			8	9.00	264	780	345	2285	TL
10.0/75 - 15.3	INDUSTRIAL		8	9.00	264	780	345	2285	TL
10.0/75 - 15.3			10	9.00	264	780	345	2285	TL
10.0/75 - 15.3			14	9.00	264	780	345	2285	TL
10.0/75 - 15.3			18	9.00	264	780	345	2285	TT
10.0/75 - 15.3			18	9.00	264	780	345	2285	TL
11.5/80 - 15.3			8	9.00	290	867	380	2540	TT
11.5/80 - 15.3			8	9.00	290	867	380	2540	TL
11.5/80 - 15.3			10	9.00	290	867	380	2540	TL
11.5/80 - 15.3			12	9.00	290	867	380	2540	TT
11.5/80 - 15.3			12	9.00	290	867	380	2540	TL
11.5/80 - 15.3			14	9.00	290	867	380	2540	TT
11.5/80 - 15.3			14	9.00	290	867	380	2540	TL
27 X 10 - 15.3			8	9.00	260	695	317	2071	TT
27 X 10 - 15.3			8	9.00	260	695	317	2071	TL
6.00 - 16			6	4.00 E	164	735	343	2190	TT
7.50 - 16			6	5.50 F	209	803	372	2393	TT
7.50 - 16			8	5.50 F	209	803	372	2393	TT
7.50 - 16			8	5.50 F	209	803	372	2393	TL
7.50 - 16	HD		8	5.50 F	209	803	372	2393	TT
9.0/70 - 16			10	W 7	222	760	355	2285	TL
270/75 - 16				9.00	250	810	0	0	TL
15.0/55 - 17			10	13.00	380	890	395	2608	TL
15.0/55 - 17			14	13.00	380	890	395	2608	TL

PRODUCT: AS 504



TECHNICAL DATA U/M: INTERNATIONAL STANDARD (MM)

Size	Version	LI/SS	PR	RIM REC	SW	OD	SLR	RC	Type
19.0/45 - 17			14	16.00	465	865	389	2578	TL
420/55 - 17			14	13.00	430	910	407	2712	TL
420/55 - 17			16	13.00	430	910	407	2712	TL
7.50 - 18			6	5.50 F	209	854	407	2649	TT
7.50 - 18			8	5.50 F	209	854	407	2649	TT
10.5/80 - 18			10	W 9	274	907	405	2657	TL
12.5/80 - 18			12	W 9	308	987	438	2892	TL
12.5/80 - 18	SPECIAL		12	W 9	308	987	438	2892	TL
12.5/80 - 18			16	W 9	308	987	438	2892	TL
12.5/80 - 18			18	W 9	308	987	438	2892	TL
7.50 - 20			8	5.50 F	209	904	422	2695	TT
16.0/70 - 20			10	13	408	1097	487	3214	TL
16.0/70 - 20			12	13	408	1097	487	3214	TL
16.0/70 - 20			14	13	408	1097	487	3214	TL
16.0/70 - 20			16	13	408	1097	487	3214	TL
400/70 - 20	INDUSTRIAL	149 A8		13	408	1097	487	3214	TL
15.5/80 - 24			10	W 12	384	1262	566	3655	TL
15.5/80 - 24			12	W 12	384	1262	566	3655	TL
15.5/80 - 24			14	W 12	384	1262	566	3655	TL
15.5/80 - 24	SPECIAL		14	W 12	384	1262	566	3655	TL
15.5/80 - 24			16	W 12	384	1262	566	3655	TL
16.5/85 - 24			10	W 13	415	1325	591	3837	TL
16.5/85 - 24			12	W 13	415	1325	591	3837	TL
16.5/85 - 24			16	W 13	415	1325	591	3837	TT
16.5/85 - 24			16	W 13	415	1325	591	3837	TL
400/80 - 24	INDUSTRIAL	156 A8		W 13	394	1262	566	3655	TL
400/80 - 24	INDUSTRIAL	162 A8		W 13	394	1262	566	3655	TL