



I-1 has been designed for field and road transport as well as for soil tillage operations with implement machinery and trailers. I-1 is a high-speed tire that optimizes travel times so that you can focus on your core business. Thanks to its flotation capability, the I-1 tire reduces soil compaction in the field and avoids damages to your valuable crops.

MACHINERY

AGRICULTURE

IMPLEMENT MACHINERY - ROTOR RAKE / TEDDER - TRAILER

APPLICATIONS

AGRICULTURE

FIELD AND ROAD TRANSPORT - HAY HARVESTING - SOIL TILLAGE

PLUS



HIGH FLOTATION CAP



REDUCED SOIL COMPACTION



HIGH SPEED



HANDLING



FUEL ECONOMY

TECHNICAL DATA U/M: INTERNATIONAL STANDARD (MM)

Size	Version	PR	RIM REC	SW	OD	SLR	RC	Type	TRA Code
9.5L - 14 SL		8	7.00	240	735	326	2154	TT	I-1
9.5L - 14 SL		8	7.00	240	735	326	2154	TL	I-1
11L - 14 SL		8	8.00	256	753	333	2206	TL	I-1
6.70 - 15 SL		6	4½ KB	172	710	319	2080	TT	I-1
6.70 - 15 SL		6	4½ KB	172	710	319	2080	TL	I-1
6.70 - 15 SL		8	4½ KB	172	710	319	2080	TT	I-1
7.60 - 15 SL		6	5.50	193	734	328	2151	TT	I-1
7.60 - 15 SL		8	5.50	193	734	328	2151	TT	I-1
7.60 - 15 SL		10	5.50	193	734	328	2151	TT	I-1
7.60 - 15 SL		10	5.50	193	734	328	2151	TL	I-1
9.5L - 15 SL		6	7.00	241	765	340	2242	TT	I-1
9.5L - 15 SL		8	7.00	241	765	340	2242	TT	I-1
9.5L - 15 SL		8	7.00	241	765	340	2242	TL	I-1
9.5L - 15 SL	STUBBLE RESISTANT	8	7.00	241	765	340	2242	TL	I-1
9.5L - 15 SL		12	7.00	241	765	340	2242	TL	I-1
9.5L - 15 SL	STUBBLE RESISTANT	12	7.00	241	765	340	2242	TL	I-1
11L - 15 SL		8	8 LB	270	770	342	2256	TT	I-1
11L - 15 SL		8	8 LB	270	770	342	2256	TL	I-1
11L - 15 SL	STUBBLE RESISTANT	8	8 LB	270	770	342	2256	TL	I-1
11L - 15 SL		10	8 LB	270	770	342	2256	TT	I-1
11L - 15 SL		10	8 LB	270	770	342	2256	TL	I-1
11L - 15 SL		12	8 LB	270	770	342	2256	TL	I-1
11L - 15 SL	STUBBLE RESISTANT	12	8 LB	270	770	342	2256	TL	I-1
12.5L - 15 SL		8	10 LB	310	820	362	2403	TT	I-1
12.5L - 15 SL		8	10 LB	310	820	362	2403	TL	I-1
12.5L - 15 SL		10	10 LB	310	820	362	2403	TT	I-1
12.5L - 15 SL		10	10 LB	310	820	362	2403	TL	I-1
12.5L - 15 SL		12	10 LB	310	820	362	2403	TT	I-1
12.5L - 15 SL		12	10 LB	310	820	362	2403	TL	I-1
12.5L - 15 SL	STUBBLE RESISTANT	12	10 LB	310	820	362	2403	TL	I-1
7.50 - 16 SL		8	5.50 F	205	785	350	2300	TT	I-1
7.50 - 16 SL	SPECIAL	8	5.50 F	205	785	350	2300	TT	I-1
7.50 - 16 SL		10	5.50 F	205	785	350	2300	TT	I-1
7.50 - 16 SL	SPECIAL	10	5.50 F	205	785	350	2300	TT	I-1
9.00 - 16 SL		10	6 LB	234	845	374	2476	TT	I-1
11L - 16 SL		8	8 LB	270	795	355	2329	TT	I-1
11L - 16 SL		10	8 LB	270	795	355	2329	TT	I-1
11L - 16 SL		12	8 LB	270	795	355	2329	TT	I-1
12.5L - 16 SL		8	10 LB	310	845	374	2476	TT	I-1
12.5L - 16 SL		10	10 LB	310	845	374	2476	TT	I-1
12.5L - 16 SL		12	10 LB	310	845	374	2476	TT	I-1
12.5L - 16 SL		12	10 LB	310	845	374	2476	TL	I-1
12.5L - 16 SL	STUBBLE RESISTANT	14	10 LB	310	845	374	2476	TL	I-1
14L - 16.1 SL		8	W 11 C	360	935	409	2740	TL	I-1
14L - 16.1 SL		12	W 11 C	360	935	409	2740	TL	I-1

PRODUCT: I - 1



TECHNICAL DATA U/M: INTERNATIONAL STANDARD (MM)

Size	Version	PR	RIM REC	SW	OD	SLR	RC	Type	TRA Code
16.5L - 16.1 SL		10	W 14 C	435	1025	444	3003	TL	I-1
19L - 16.1 SL		10	W 16 C	490	1100	474	3223	TL	I-1
19L - 16.1 SL		12	W 16 C	490	1100	474	3223	TL	I-1
19L - 16.1 SL		14	W 16 C	490	1100	474	3223	TL	I-1
21.5L - 16.1 SL		8	W 18 CH	550	1130	485	3311	TL	I-1
21.5L - 16.1 SL		14	W 18 CH	550	1130	485	3311	TL	I-1
9.00 - 24 SL		8	W 8 H	272	1094	0	0	TL	I-1
11.25 - 24 SL		8	W 10 H	325	1171	0	0	TL	I-1