

TF 9090



TF 9090 is a field-oriented tire designed for 2WD tractors in soil tillage operations. Its “special” version ensures extra puncture resistance for tire usage in critical conditions.

MACHINERY

 AGRICULTURE

2WD TRACTOR

APPLICATIONS

 AGRICULTURE

SOIL TILLAGE

PLUS



FIELD PROTECTION

PRODUCT: TF 9090



TECHNICAL DATA U/M: INTERNATIONAL STANDARD (MM)

Size	Version	LI/SS	PR	RIM REC	SW	OD	SLR	RC	Type	TRA Code
4.00 - 12		60 A6	4	3.00 D	112	530	255	1573	TT	F-2
4.00 - 12		68 A6	6	3.00 D	112	530	255	1573	TT	F-2
5.00 - 15		73 A6	4	4.00 E	140	655	307	1951	TT	F-2
5.00 - 15		82 A6	6	4.00 E	140	655	307	1951	TT	F-2
4.00 - 16		69 A6	4	3.00 D	112	630	301	1877	TT	F-2
5.50 - 16		86 A6	6	4.00 E	150	710	332	2116	TT	F-2
6.00 - 16		88 A6	6	4.50 E	170	735	346	2190	TT	F-2
6.00 - 16	SPECIAL	88 A6	6	4.50 E	170	735	346	2190	TT	F-2
6.00 - 16		94 A6	8	4.50 E	170	735	346	2190	TT	F-2
6.00 - 16	SPECIAL	94 A6	8	4.50 E	170	735	346	2190	TT	F-2
6.50 - 16		91 A6	6	4.50 E	180	765	359	2280	TT	F-2
6.50 - 16		98 A6	8	4.50 E	180	765	359	2280	TT	F-2
7.50 - 16		98 A6	6	5.50 F	207	810	379	2414	TT	F-2
7.50 - 16	SPECIAL	98 A6	6	5.50 F	207	810	379	2414	TT	F-2
7.50 - 16		103 A6	8	5.50 F	207	810	379	2414	TT	F-2
7.50 - 16	SPECIAL	103 A6	8	5.50 F	207	810	379	2414	TT	F-2
7.50 - 16		109 A6	10	5.50 F	207	810	379	2414	TT	F-2
9.00 - 16		111 A6	8	W 8	257	855	398	2548	TT	F-2
9.00 - 16		116 A6	10	W 8	257	855	398	2548	TT	F-2
9.00 - 16	SPECIAL	116 A6	10	W 8	257	855	398	2548	TT	F-2
10.00 - 16		115 A6	8	W 8	275	900	418	2682	TT	F-2
10.00 - 16	SPECIAL	115 A6	8	W 8	275	900	418	2682	TT	F-2
10.00 - 16		119 A6	10	W 8	275	900	418	2682	TT	F-2
10.00 - 16	SPECIAL	119 A6	10	W 8	275	900	418	2682	TT	F-2
11.00 - 16		118 A6	8	W 10 L	320	970	448	2890	TT	F-2
11.00 - 16		118 A6	8	W 10 L	320	970	448	2890	TL	F-2
11.00 - 16	SPECIAL	118 A6	8	W 10 L	320	970	448	2890	TT	F-2
7.50 - 18		101 A6	6	5.50 F	207	860	404	2562	TT	F-2
7.50 - 18	SPECIAL	101 A6	6	5.50 F	207	860	404	2562	TT	F-2
7.50 - 18		106 A6	8	5.50 F	207	860	404	2562	TT	F-2
7.50 - 18	SPECIAL	106 A6	8	5.50 F	207	860	404	2562	TT	F-2
7.50 - 18		113 A6	10	5.50 F	207	860	404	2562	TT	F-2
4.00 - 19		72 A6	4	3.00 D	115	715	343	2145	TT	F-2
6.00 - 19		93 A6	6	4.50 E	167	815	386	2445	TT	F-2
7.50 - 20		103 A6	6	5.50 F	205	915	431	2725	TT	F-2
7.50 - 20	SPECIAL	103 A6	6	5.50 F	205	915	431	2725	TT	F-2
7.50 - 20		109 A6	8	5.50 F	205	915	431	2725	TT	F-2
7.50 - 20	SPECIAL	109 A6	8	5.50 F	205	915	431	2725	TT	F-2