



TR 135 is best suitable for soil tillage and spraying applications. Some sizes and versions are also suitable for excavators, trailers and harvesters. Traction, self-cleaning properties and stability are key features which make the TR 135 tire the ideal partner even on the most difficult ground conditions.

MACHINERY

 AGRICULTURE

TRACTOR - TRAILER

APPLICATIONS

 AGRICULTURE

SOIL TILLAGE -

PLUS



TRACTION



STABILITY



SELF CLEANING

PRODUCT: TR 135



TECHNICAL DATA U/M: INTERNATIONAL STANDARD (MM)

Size	Version	LI/SS	PR	RIM REC	SW	OD	SLR	RC	Type	TRA Code
8.00 - 20		105 A6	6	5.50 F	225	965	448	2837	TT	R-1
8.00 - 20		111 A6	8	5.50 F	225	965	448	2837	TT	R-1
9.5 - 20		102 A6	6	W 8	240	955	444	2913	TT	R-1
9.5 - 20		107 A6	8	W 8	240	955	444	2913	TT	R-1
9.5 - 20	HD	107 A6	8	W 8	240	955	444	2913	TT	R-1
10.00 - 20		152 A2	10	7.5	280	1075	495	3160	TT	R-1
11.2 - 20		111 A6	8	W 10	292	1020	477	3000	TT	R-1
12.4 - 20		116 A6	8	W 11	325	1075	500	3160	TT	R-1
12.4 - 20	HD	116 A6	8	W 11	325	1075	500	3160	TT	R-1
8.3 - 24		100 A6	6	W 7	211	995	469	2925	TT	R-1
8.3 - 24		105 A6	8	W 7	211	995	469	2925	TT	R-1
8.3 - 24	HD	105 A6	8	W 7	211	995	469	2925	TT	R-1
9.5 - 24		106 A6	6	W 8	232	1056	502	3234	TT	R-1
9.5 - 24		112 A6	8	W 8	232	1056	502	3234	TT	R-1
9.5 - 24	HD	112 A6	8	W 8	232	1056	502	3234	TT	R-1
9.5 - 24		116 A6	10	W 8	232	1056	502	3234	TT	R-1
9.5 - 24	HD	116 A6	10	W 8	232	1056	502	3234	TT	R-1
11.2 - 24		110 A6	6	W 10	284	1105	517	3398	TT	R-1
11.2 - 24		116 A6	8	W 10	284	1105	517	3398	TT	R-1
11.2 - 24		116 A6	8	W 10	284	1105	517	3398	TL	R-1
11.2 - 24	HD	116 A6	8	W 10	284	1105	517	3398	TT	R-1
11.2 - 24	HD	120 A6	10	W 10	284	1105	517	3398	TT	R-1
12.4 - 24		115 A6	6	W 11	315	1160	543	3573	TT	R-1
12.4 - 24		121 A6	8	W 11	315	1160	543	3573	TT	R-1
12.4 - 24		121 A6	8	W 11	315	1160	543	3573	TL	R-1
12.4 - 24	HD	121 A6	8	W 11	315	1160	543	3573	TT	R-1
12.4 - 24	HD	121 A6	8	W 11	315	1160	543	3573	TL	R-1
12.4 - 24		125 A6	10	W 11	315	1160	543	3573	TT	R-1
12.4 - 24		128 A6	12	W 11	315	1160	543	3573	TT	R-1
12.4 - 24	SPECIAL	128 A6	12	W 11	315	1160	543	3573	TT	R-1
13.6 - 24		123 A6	8	W 12	345	1220	562	3698	TT	R-1
13.6 - 24		123 A6	8	W 12	345	1220	562	3698	TL	R-1
13.6 - 24	HD	123 A6	8	W 12	345	1220	562	3698	TT	R-1
13.6 - 24		130 A6	12	W 12	345	1220	562	3698	TT	R-1
14.9 - 24		128 A6	8	W 13	378	1265	576	3837	TT	R-1
14.9 - 24		128 A6	8	W 13	378	1265	576	3837	TL	R-1
14.9 - 24	HD	128 A6	8	W 13	378	1265	576	3837	TT	R-1
14.9 - 24	HD	132 A6	10	W 13	378	1265	576	3837	TL	R-1
14.9 - 24		135 A6	12	W 13	378	1265	576	3837	TT	R-1
14.9 - 24		135 A6	12	W 13	378	1265	576	3837	TL	R-1
16.9 - 24		133 A6	8	W 15 L	429	1335	613	3925	TT	R-1
16.9 - 24	HD	133 A6	8	W 15 L	429	1335	613	3925	TT	R-1
16.9 - 24		136 A6	10	W 15 L	429	1335	613	3925	TT	R-1
16.9 - 24	HD	140 A6	12	W 15 L	429	1335	613	3925	TT	R-1
14.9 - 26		129 A6	8	W 13	375	1315	608	3863	TT	R-1

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints.

All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..

PRODUCT: TR 135



TECHNICAL DATA U/M: INTERNATIONAL STANDARD (MM)

Size	Version	LI/SS	PR	RIM REC	SW	OD	SLR	RC	Type	TRA Code
14.9 - 26	HD	129 A6	8	W 13	375	1315	608	3863	TT	R-1
14.9 - 26		136 A6	12	W 13	375	1315	608	3863	TT	R-1
16.9 - 26		137 A6	10	W 15 L	430	1380	625	4183	TT	R-1
16.9 - 26		140 A6	12	W 15 L	430	1380	625	4183	TT	R-1
23.1 - 26		153 A6	12	DW 20 B ; DW 20 A	587	1585	700	4615	TL	R-1
23.1 - 26		153 A6	12	DW 20 B ; DW 20 A	587	1585	700	4615	TT	R-1
23.1 - 26	DUAL BEAD	153 A6	12	DW 20 B ; DW 20 A	587	1585	700	4615	TL	R-1
23.1 - 26		156 A6	14	DW 20 B ; DW 20 A	587	1585	700	4615	TL	R-1
23.1 - 26		159 A6	16	DW 20 B ; DW 20 A	587	1585	700	4615	TL	R-1
23.1 - 26		159 A6	16	DW 20 B ; DW 20 A	587	1585	700	4615	TT	R-1
23.1 - 26		159 A6	16	DW 20 B ; DW 20 A	587	1585	700	4615	TT	R-1
23.1 - 26	DUAL BEAD	159 A6	16	DW 20 B ; DW 20 A	587	1585	700	4615	TL	R-1
23.1 - 26	DUAL BEAD HD	159 A6	16	DW 20 B ; DW 20 A	587	1585	700	4615	TL	R-1
23.1 - 26	DUAL BEAD	161 A6	18	DW 20 B ; DW 20 A	587	1585	700	4615	TL	R-1
8.3 - 28		103 A6	6	W 7	213	1104	523	3246	TT	R-1
8.3 - 28		108 A6	8	W 7	213	1104	523	3246	TT	R-1
9.5 - 28		108 A6	6	W 8	235	1155	542	3381	TT	R-1
9.5 - 28		114 A6	8	W 8	235	1155	542	3381	TT	R-1
11.2 - 28		118 A6	8	W 10	284	1205	565	3543	TT	R-1
11.2 - 28	HD	118 A6	8	W 10	284	1205	565	3543	TT	R-1
11.2 - 28		122 A6	10	W 10	284	1205	565	3543	TT	R-1
12.4 - 28		117 A6	6	W 11	325	1260	584	3876	TT	R-1
12.4 - 28		123 A6	8	W 11	325	1260	584	3876	TT	R-1
12.4 - 28	HD	123 A6	8	W 11	325	1260	584	3876	TT	R-1
12.4 - 28		127 A6	10	W 11	325	1260	584	3876	TT	R-1
12.4 - 28		131 A6	12	W 11	325	1260	584	3876	TT	R-1
13.6 - 28		125 A6	8	W 12	345	1310	614	4031	TT	R-1
13.6 - 28	HD	125 A6	8	W 12	345	1310	614	4031	TT	R-1
13.6 - 28		134 A6	12	W 12	345	1310	614	4031	TT	R-1
13.6 - 28		137 A6	14	W 12	345	1310	614	4031	TT	R-1
14.9 - 28		125 A6	6	W 13	378	1365	634	4013	TT	R-1
14.9 - 28		130 A6	8	W 13	378	1365	634	4013	TT	R-1
14.9 - 28		130 A6	8	W 13	378	1365	634	4013	TL	R-1
14.9 - 28	HD	130 A6	8	W 13	378	1365	634	4013	TT	R-1
14.9 - 28		137 A6	12	W 13	378	1365	634	4013	TT	R-1
14.9 - 28	HD	137 A6	12	W 13	378	1365	634	4013	TT	R-1
14.9 - 28		139 A6	14	W 13	378	1365	634	4013	TT	R-1
18.4 - 28		138 A6	8	W 16 L	467	1501	691	4413	TL	R-1
18.4 - 28		147 A6	12	W 16 L	467	1501	691	4413	TL	R-1
7.2 - 30		95 A6	6	W 6	185	1095	523	3219	TT	R-1
9.5 - 30		109 A6	6	W 8	241	1200	567	3528	TT	R-1
9.5 - 30		115 A6	8	W 8	241	1200	567	3528	TT	R-1
14.9 - 30		131 A6	8	W 13	378	1415	659	4316	TT	R-1
15 - 30		149 A6	12	W 16 L	460	1545	714	4542	TT	R-1

PRODUCT: TR 135



TECHNICAL DATA U/M: INTERNATIONAL STANDARD (MM)

Size	Version	LI/SS	PR	RIM REC	SW	OD	SLR	RC	Type	TRA Code
15 - 30		151 A6	14	W 16 L	460	1545	714	4542	TT	R-1
16.9 - 30		137 A6	8	W 15 L	429	1485	678	4535	TT	R-1
16.9 - 30		139 A6	10	W 15 L	429	1485	678	4535	TT	R-1
16.9 - 30		146 A6	14	W 15 L	429	1485	678	4535	TT	R-1
18.4 - 30		139 A6	8	W 16 L	460	1545	697	4712	TT	R-1
18.4 - 30	HD	139 A6	8	W 16 L	460	1545	697	4712	TT	R-1
18.4 - 30		145 A6	10	W 16 L	460	1545	697	4712	TT	R-1
18.4 - 30	HD	145 A6	10	W 16 L	460	1545	697	4712	TT	R-1
18.4 - 30	HD	145 A6	10	W 16 L	460	1545	697	4712	TL	R-1
18.4 - 30		149 A6	12	W 16 L	460	1545	697	4712	TT	R-1
18.4 - 30		149 A6	12	W 16 L	460	1545	697	4712	TL	R-1
18.4 - 30	HD	149 A6	12	W 16 L	460	1545	697	4712	TT	R-1
18.4 - 30		151 A6	14	W 16 L	460	1545	697	4712	TT	R-1
23.1 - 30		146 A6	8	DW 20 B ; DW 20 A	600	1700	780	4998	TT	R-1
23.1 - 30		146 A6	8	DW 20 B ; DW 20 A	600	1700	780	4998	TL	R-1
23.1 - 30		155 A6	12	DW 20 B ; DW 20 A	600	1700	780	4998	TT	R-1
23.1 - 30		155 A6	12	DW 20 B ; DW 20 A	600	1700	780	4998	TL	R-1
23.1 - 30	DUAL BEAD	155 A6	12	DW 20 B ; DW 20 A	600	1700	780	4998	TT	R-1
23.1 - 30	DUAL BEAD	164 A6	18	DW 20 B ; DW 20 A	600	1700	780	4998	TT	R-1
23.1 - 30	DUAL BEAD	164 A6	18	DW 20 B ; DW 20 A	600	1700	780	4998	TL	R-1
8.3 - 32		105 A6	6	W 7	211	1195	572	3585	TT	R-1
8.3 - 32		111 A6	8	W 7	211	1195	572	3585	TT	R-1
9.5 - 32		110 A6	6	W 8	235	1255	594	3686	TT	R-1
12.4 - 32		119 A6	6	W 11	325	1360	639	3998	TT	R-1
12.4 - 32		124 A6	8	W 11	325	1360	639	3998	TT	R-1
12.4 - 32	HD	124 A6	8	W 11	325	1360	639	3998	TT	R-1
16.9 - 34		139 A6	8	W 15 L	429	1585	728	4794	TT	R-1
16.9 - 34	HD	139 A6	8	W 15 L	429	1585	728	4794	TT	R-1
16.9 - 34		142 A6	10	W 15 L	429	1585	728	4794	TT	R-1
16.9 - 34	HD	142 A6	10	W 15 L	429	1585	728	4794	TT	R-1
16.9 - 34		144 A6	12	W 15 L	429	1585	728	4794	TT	R-1
16.9 - 34	HD	144 A6	12	W 15 L	429	1585	728	4794	TT	R-1
18.4 - 34		137 A6	6	W 16 L	467	1650	751	5009	TT	R-1
18.4 - 34		142 A6	8	W 16 L	467	1650	751	5009	TT	R-1
18.4 - 34	HD	142 A6	8	W 16 L	467	1650	751	5009	TT	R-1
18.4 - 34		146 A6	10	W 16 L	467	1650	751	5009	TT	R-1
18.4 - 34	HD	146 A6	10	W 16 L	467	1650	751	5009	TT	R-1
18.4 - 34		151 A6	12	W 16 L	467	1650	751	5009	TT	R-1
18.4 - 34	HD	151 A6	12	W 16 L	467	1650	751	5009	TT	R-1
18.4 - 34	HD SPECIAL	151 A6	12	W 16 L	467	1650	751	5009	TT	R-1
18.4 - 34		154 A6	14	W 16 L	467	1650	751	5009	TT	R-1
18.4 - 34	HD	154 A6	14	W 16 L	467	1650	751	5009	TT	R-1
23.1 - 34		153 A6	10	DW 20 B ; DW 20 A	585	1810	834	5321	TT	R-1
23.1 - 34		153 A6	10	DW 20 B ; DW 20 A	585	1810	834	5321	TL	R-1
8.3 - 36		107 A6	6	W 7	211	1295	628	4028	TT	R-1

PRODUCT: TR 135



TECHNICAL DATA U/M: INTERNATIONAL STANDARD (MM)

Size	Version	LI/SS	PR	RIM REC	SW	OD	SLR	RC	Type	TRA Code
8.3 - 36		113 A6	8	W 7	211	1295	628	4028	TT	R-1
9.5 - 36		122 A6	10	W 8	235	1360	646	4000	TT	R-1
12.4 - 36		126 A6	8	W 11	325	1465	691	4307	TT	R-1
12.4 - 36	HD	126 A6	8	W 11	325	1465	691	4307	TT	R-1
12.4 - 36		131 A6	10	W 11	325	1465	691	4307	TT	R-1
12.4 - 36	HD	131 A6	10	W 11	325	1465	691	4307	TT	R-1
12.4 - 36		135 A6	12	W 11	325	1465	691	4307	TT	R-1
12.4 - 36		139 A6	14	W 11	325	1465	691	4307	TT	R-1
12.4 - 36	HD	139 A6	14	W 11	325	1465	691	4307	TL	R-1
12.4 - 36	HD	139 A6	14	W 11	325	1465	691	4307	TT	R-1
13.6 - 36		125 A6	6	W 12	345	1515	713	4454	TT	R-1
13.6 - 36		129 A6	8	W 12	345	1515	713	4454	TT	R-1
13.6 - 36		134 A6	10	W 12	345	1515	713	4454	TT	R-1
13.6 - 36	HD	134 A6	10	W 12	345	1515	713	4454	TT	R-1
12.4 - 38		127 A6	8	W 11	315	1525	718	4670	TT	R-1
12.4 - 38		138 A6	14	W 11	315	1525	718	4670	TT	R-1
12.4 - 38		138 A6	14	W 11	315	1525	718	4670	TL	R-1
13.6 - 38		131 A6	8	W 12	345	1565	735	4832	TT	R-1
13.6 - 38	HD	131 A6	8	W 12	345	1565	735	4832	TT	R-1
13.6 - 38		139 A6	12	W 12	345	1565	735	4832	TT	R-1
13.6 - 38	HD	139 A6	12	W 12	345	1565	735	4832	TT	R-1
13.6 - 38		142 A6	14	W 12	345	1565	735	4832	TT	R-1
14.00 - 38		131 A6	8	W 12	345	1565	735	4832	TT	R-1
14.00 - 38	SPECIAL	139 A6	12	W 12	345	1565	735	4832	TT	R-1
15.5 - 38		133 A6	8	W 14 L	395	1585	746	4660	TT	R-1
15.5 - 38	HD	133 A6	8	W 14 L	395	1585	746	4660	TT	R-1
15.5 - 38		138 A6	10	W 14 L	395	1585	746	4660	TT	R-1
15.5 - 38	HD	138 A6	10	W 14 L	395	1585	746	4660	TT	R-1
15.5 - 38		141 A6	12	W 14 L	395	1585	746	4660	TT	
16.9 - 38		141 A6	8	W 15 L	429	1685	788	4954	TT	R-1
16.9 - 38	HD	141 A6	8	W 15 L	429	1685	788	4954	TT	R-1
16.9 - 38		143 A6	10	W 15 L	429	1685	788	4954	TT	R-1
16.9 - 38	HD	143 A6	10	W 15 L	429	1685	788	4954	TT	R-1
16.9 - 38		146 A6	12	W 15 L	429	1685	788	4954	TT	R-1
18.4 - 38		143 A6	8	W 16 L	467	1750	816	5145	TT	R-1
18.4 - 38	HD	143 A6	8	W 16 L	467	1750	816	5145	TT	R-1
18.4 - 38	HD	148 A6	10	W 16 L	467	1750	816	5145	TT	R-1
18.4 - 38	HD	148 A6	10	W 16 L	467	1750	816	5145	TL	R-1
18.4 - 38		153 A6	12	W 16 L	467	1750	816	5145	TT	R-1
18.4 - 38		153 A6	12	W 16 L	467	1750	816	5145	TL	R-1
18.4 - 38	HD	153 A6	12	W 16 L	467	1750	816	5145	TT	R-1
20.8 - 38		148 A6	8	W 18 L	530	1835	852	5395	TT	R-1
20.8 - 38		156 A6	12	W 18 L	530	1835	852	5395	TT	R-1
20.8 - 38		156 A6	12	W 18 L	530	1835	852	5395	TL	R-1
20.8 - 38	HD	156 A6	12	W 18 L	530	1835	852	5395	TT	R-1

PRODUCT: TR 135



TECHNICAL DATA U/M: INTERNATIONAL STANDARD (MM)

Size	Version	LI/SS	PR	RIM REC	SW	OD	SLR	RC	Type	TRA Code
20.8 - 38		160 A6	14	W 18 L	530	1835	852	5395	TT	R-1
20.8 - 38	DUAL BEAD HD	163 A6	16	W 18 L	530	1835	852	5395	TT	R-1
20.8 - 38	DUAL BEAD HD	166 A6	18	W 18 L	530	1835	852	5395	TT	R-1
9.5 - 42		125 A6	10	W 8	246	1510	721	4663	TT	R-1
12.4 - 42		134 A6	10	W 10 ; W 10 A	322	1630	770	5011	TL	
20.8 - 42		157 A6	12	W 18 L	535	1950	909	5733	TT	R-1
20.8 - 42		157 A6	12	W 18 L	535	1950	909	5733	TL	R-1