

TR 136



TR 136 has been developed by BKT to equip tractors and trailers in soil tillage and transport operations. This tire provides improved traction in all working conditions along with best cut and chip resistance to reduce machine downtime and increase your productivity.

MACHINERY

 AGRICULTURE

TRACTOR - TRAILER

APPLICATIONS

 AGRICULTURE

HAULAGE - SOIL TILLAGE

PLUS



TRACTION



CUT & CHIP
RESISTANCE



HEAVY DUTY SERVICE

PRODUCT: TR 136



TECHNICAL DATA U/M: INTERNATIONAL STANDARD (MM)

Size	Version	LI/SS	PR	RIM REC	SW	OD	SLR	RC	Type	TRA Code
18.4 - 26		146 A6	12	W 16 L	480	1450	646	4205	TL	R-1
18.4 - 26		146 A6	12	W 16 L	480	1450	646	4205	TT	R-1
18.4 - 26	SPECIAL	146 A6	12	W 16 L	480	1450	646	4205	TL	R-1
12.4 - 28		123 A6	8	W 11	315	1275	595	3749	TT	R-1
16.9 - 30		137 A6	8	W 15 L	429	1485	687	4501	TT	R-1
16.9 - 30	HD	137 A6	8	W 15 L	429	1485	687	4501	TT	R-1
16.9 - 30	SPECIAL	137 A6	8	W 15 L	429	1485	687	4501	TT	R-1
16.9 - 30		139 A6	10	W 15 L	429	1485	687	4501	TT	R-1
16.9 - 30		143 A6	12	W 15 L	429	1485	687	4501	TT	R-1
16.9 - 30	SPECIAL	143 A6	12	W 15 L	429	1485	687	4501	TT	R-1
18.4 - 30		139 A6	8	W 16 L	465	1545	707	4741	TT	R-1
18.4 - 30	HD	139 A6	8	W 16 L	465	1545	707	4741	TT	R-1
18.4 - 30	HD	149 A6	12	W 16 L	465	1545	707	4741	TT	R-1
18.4 - 30	SPECIAL	149 A6	12	W 16 L	465	1545	707	4741	TT	R-1
18.4 - 30	HD	151 A6	14	W 16 L	465	1545	707	4741	TT	R-1