



TR 137 is BKT's most suitable tire for all harvesting operations. It ensures high flotation capability along with low soil compaction and excellent traction in the field. The tire is available in different versions: the "aramid-belted" version provides better puncture resistance and protection against all typical damages of this application; the "HD" version is for high load capacity to improve today's farmers' requirements in terms of productivity.

## MACHINERY

 **AGRICULTURE**

HARVESTER

## APPLICATIONS

 **AGRICULTURE**

HARVESTING

## PLUS



TRACTION



HIGH FLOTATION CAP



HEAVY DUTY SERVICE



COMFORT

PRODUCT: TR 137



TECHNICAL DATA U/M: INTERNATIONAL STANDARD (MM)

Size	Version	LI/SS	PR	RIM REC	SW	OD	SLR	RC	Type	TRA Code
24.5 - 32		159 A6	12	DW 21 B	622	1805	807	5343	TL	R-1
24.5 - 32		163 A6	14	DW 21 B	622	1805	807	5343	TL	R-1
30.5L - 32		162 A6	12	DH 27 B	770	1865	831	5520	TL	R-1
30.5L - 32		164 A6	14	DH 27 B	770	1865	831	5520	TL	R-1
30.5L - 32		167 A6	16	DH 27 B	770	1865	831	5520	TL	R-1
30.5L - 32	ARAMID BELTED	170 A6	18	DH 27 B	770	1865	831	5520	TL	R-1
30.5L - 32	HD	170 A6	18	DH 27 B	770	1865	831	5520	TL	R-1