

TR 144



TR 144 is suitable to equip small tractors to be used in soil tillage operations. It has been specially designed for wet conditions as you can find on wet and loose soil, and paddy fields. TR 144 ensures outstanding performance in all operating conditions which require both excellent traction and self-cleaning features. TR 144 is also available in a “special” version, which is best suitable for heavy-duty service.

MACHINERY

 AGRICULTURE

SMALL TRACTOR

APPLICATIONS

 AGRICULTURE

SOIL TILLAGE

PLUS



TRACTION



SUITABLE FOR MUDDY
GROUND



SELF CLEANING



COMFORT

PRODUCT: TR 144



TECHNICAL DATA U/M: INTERNATIONAL STANDARD (MM)

Size	Version	LI/SS	PR	RIM REC	SW	OD	SLR	RC	Type	TRA Code
7 - 16		75 A6	4	6 L ; 6 LB ; 6.00 F	183	740	345	2217	TT	R-1
7 - 16		75 A6	4	6 L ; 6 LB ; 6.00 F	183	740	345	2217	TL	R-1
7 - 16		84 A6	6	6 L ; 6 LB ; 6.00 F	183	740	345	2217	TT	R-1
8 - 16		83 A6	4	6 L ; 6 LB ; 6.00 F	200	785	366	2360	TT	
8 - 16		91 A6	6	6 L ; 6 LB ; 6.00 F	200	785	366	2360	TT	R-1
8 - 16		91 A6	6	6 L ; 6 LB ; 6.00 F	200	785	366	2360	TL	R-1
8 - 16	SPECIAL	91 A6	6	6 L ; 6 LB ; 6.00 F	200	785	366	2360	TT	R-1
8 - 16		98 A6	8	6 L ; 6 LB ; 6.00 F	200	785	366	2360	TT	R-1
9.5 - 16		96 A6	6	W 8 L	245	850	392	2542	TT	R-1
9.5 - 16		96 A6	6	W 8 L	245	850	392	2542	TL	R-1
9.5 - 16		102 A6	8	W 8 L	245	850	392	2542	TT	R-1
9.5 - 16		102 A6	8	W 8 L	245	850	392	2542	TL	R-1
8 - 18		85 A6	4	W 6	200	840	391	2431	TT	R-1
8 - 18		94 A6	6	W 6	200	840	391	2431	TT	R-1
8 - 18	SPECIAL	94 A6	6	W 6	200	840	391	2431	TT	R-1
8 - 18		100 A6	8	W 6	200	840	391	2431	TT	R-1
8 - 18	SPECIAL	100 A6	8	W 6	200	840	391	2431	TT	R-1
8.3 - 20		96 A6	6	W 7	211	890	414	2670	TT	R-1
9.5 - 22		104 A6	6	W 7	235	1000	458	2985	TT	R-1