

TR 171



TR 171 is a deep tread tire suitable for tractors in soil tillage operations. Thanks to its outstanding self-cleaning properties, it is ideal for wet and moist soil. Also in the harshest operating conditions, TR 171 provides excellent traction and extraordinary durability.

MACHINERY

 AGRICULTURE

TRACTOR

APPLICATIONS

 AGRICULTURE

SOIL TILLAGE WET / MOIST SOIL

PLUS



TRACTION



SUITABLE FOR MUDDY
GROUND



SELF CLEANING



DURABILITY



DEEP TREAD

PRODUCT: TR 171



TECHNICAL DATA U/M: INTERNATIONAL STANDARD (MM)

Size	Version	LI/SS	PR	RIM REC	SW	OD	SLR	RC	Type	TRA Code	
5.00 - 12		61 A6	4	3.00 D DT ; 3.00 D	130	580	271	1731	TT	R-1W+	
5.00 - 12		67 A6	6	3.00 D DT ; 3.00 D	130	580	271	1731	TT	R-1W+	
6.00 - 12		76 A6	6	4.00 E DT ; 4.00 E	160	635	293	1901	TT	R-1W+	
9.5 - 16		96 A6	6	W 8 L	241	845	392	2499	TT	R-1W+	
8 - 18		85 A6	4	W 6	190	845	390	2515	TT	R-1W+	
8 - 18		94 A6	6	W 6	190	845	390	2525	TT	R-1W+	
9.5 - 18		105 A6	8	W 8	241	900	417	2646	TT	R-1W+	
8.3 - 20		96 A6	6	W 7	200	895	419	2795	TT	R-1W+	
8.3 - 20		101 A6	8	W 7	200	895	419	2795	TT	R-1W+	
9.5 - 20		101 A6	6	W 8	235	950	442	2835	TT	R-1W+	
9.5 - 20		107 A6	8	W 8	235	950	442	2835	TT	R-1W+	
11.2 - 20		113 A6	8	W 10	285	1005	465	3000	TT	R-1W+	
8.3 - 22		104 A6	8	W 7	205	945	444	2778	TT	R-1W+	
9.5 - 22		110 A6	8	W 8	235	1005	469	2955	TT	R-1W+	
8.3 - 24		100 A6	6	W 7	200	1005	470	3065	TT	R-1W+	
8.3 - 24		105 A6	8	W 7	200	1005	470	2970	TT	R-1W+	
9.5 - 24		106 A6	6	W 8	236	1066	500	3260	TT	R-1W+	
9.5 - 24		111 A6	8	W 8	236	1066	500	3260	TT	R-1W+	
11.2 - 24		110 A6	6	W 10	285	1105	519	3388	TT	R-1W+	
11.2 - 24		116 A6	8	W 10	285	1105	519	3388	TT	R-1W+	
11.2 - 24		116 A6	10	W 10	285	1105	519	3388	TT	R-1W+	
12.4 - 24		106 A6	4	W 11	315	1165	544	3557	TT	R-1W+	
12.4 - 24		115 A6	6	W 11	315	1165	544	3557	TT	R-1W+	
12.4 - 24		120 A6	8	W 11	315	1165	544	3557	TT	R-1W+	
12.4 - 24	HD	120 A6	8	W 11	315	1165	544	3557	TT	R-1W+	
13.6 - 24		119 A6	6	W 12	355	1210	562	3657	TT	R-1W+	
13.6 - 24		123 A6	8	W 12	355	1210	562	3657	TT	R-1W+	
14.9 - 24		123 A6	6	W 13	391	1265	575	3792	TT	R-1W+	
14.9 - 24		128 A6	8	W 13	391	1265	575	3792	TT	R-1W+	
11.2 - 26		117 A6	8	W 10	284	1155	540	3396	TT	R-1W+	
12.4 - 26		121 A6	8	W 11	315	1210	573	3727	TT	R-1W+	
13.6 - 26		110 A6	4	W 12	340	1270	580	3774	TT	R-1W+	
13.6 - 26		120 A6	6	W 12	340	1270	580	3774	TT	R-1W+	
13.6 - 26		126 A6	8	W 12	340	1270	589	3785	TT	R-1W+	
12.4 - 28		117 A6	6	W 11	315	1260	589	3860	TT	R-1W+	
12.4 - 28		123 A6	8	W 11	315	1260	589	3860	TT	R-1W+	
12.4 - 28		131 A6	12	W 11	315	1260	589	3860	TT	R-1W+	
13.6 - 28		112 A6	4	W 12	350	1300	614	4013	TT	R-1W+	
13.6 - 28		121 A6	6	W 12	350	1300	614	4013	TT	R-1W+	
13.6 - 28		125 A6	8	W 12	350	1300	614	4013	TT	R-1W+	
13.6 - 28	HD	125 A6	8	W 12	350	1300	614	4013	TT	R-1W+	
13.6 - 28		134 A6	12	W 12	350	1300	614	4013	TT	R-1W+	
14.9 - 28		130 A6	8	W 13	388	1361	626	4154	TT	R-1W+	
14.9 - 28	HD	130 A6	8	W 13	388	1361	626	4154	TT	R-1W+	
14.9 - 28		137 A6	12	W 13	388	1361	626	4154	TT	R-1W+	

PRODUCT: TR 171



TECHNICAL DATA U/M: INTERNATIONAL STANDARD (MM)

Size	Version	LI/SS	PR	RIM REC	SW	OD	SLR	RC	Type	TRA Code	
14.9 - 28	HD	137 A6	12	W 13	388	1361	626	4154	TT	R-1W+	
16.9 - 28		135 A6	8	W 15 L	435	1440	663	4387	TT	R-1W+	
16.9 - 28		143 A6	12	W 15 L	435	1440	663	4387	TT	R-1W+	
14.9 - 30		131 A6	8	W 13	380	1415	659	4160	TT	R-1W+	
16.9 - 30		137 A6	8	W 15 L	430	1490	687	4535	TT	R-1W+	
16.9 - 30		143 A6	12	W 15 L	430	1490	687	4535	TT	R-1W+	
18.4 - 30		145 A6	10	W 16 L	470	1550	710	4706	TT	R-1W+	
12.4 - 32		124 A6	8	W 11	315	1370	643	4232	TT	R-1W+	
16.9 - 34		139 A6	8	W 15 L	429	1585	736	4838	TT	R-1W+	
18.4 - 34		146 A6	10	W 16 L	470	1655	768	4866	TT	R-1W+	
12.4 - 36		126 A6	8	W 11	315	1470	691	4332	TT	R-1W+	
13.6 - 36		129 A6	8	W 12	345	1520	717	4647	TT	R-1W+	
13.6 - 38		131 A6	8	W 12	345	1585	738	4769	TT	R-1W+	
16.9 - 38		141 A6	8	W 15 L	429	1685	788	4954	TT	R-1W+	
18.4 - 38		148 A6	10	W 16 L	470	1760	815	5364	TT	R-1W+	