



TR 387 is an agro-industrial tire suitable for trailers. It features outstanding flotation capability and is available in different versions to meet specific user requirements in terms of cut and chip resistance, heavy-duty services and durability. The "dual bead" version is particularly suitable for industrial tractors and transport operations on trailers.

## MACHINERY

 **AGRICULTURE**

TRAILER

 **INDUSTRIAL**

COMPACTOR - TRAILER

## APPLICATIONS

 **AGRICULTURE**

HAULAGE

 **INDUSTRIAL**

COMPACTING - HAULAGE

## PLUS



**AGRO-INDUSTRIAL USE**



**HIGH FLOTATION CAP**

PRODUCT: TR 387



TECHNICAL DATA U/M: INTERNATIONAL STANDARD (MM)

Size	Version	LI/SS	PR	RIM REC	SW	OD	SLR	RC	Type	TRA Code	
18.4 - 26		142 A6	10	DW 16 L	475	1430	635	4150	TL	R-3	
18.4 - 26		146 A6	12	DW 16 L	475	1430	635	4150	TL	R-3	
18.4 - 26	HD	152 A6	16	DW 16 L	475	1430	635	4150	TL	R-3	
23.1 - 26		145 A6	8	DW 20 B	587	1560	690	4545	TL	R-3	
23.1 - 26		153 A6	12	DW 20 B	587	1560	690	4545	TL	R-3	
23.1 - 26	HD	164 A6	12	DW 20 B	587	1560	690	4545	TL	R-3	
23.1 - 26		159 A6	16	DW 20 B	587	1560	690	4545	TL	R-3	
23.1 - 26	DUAL BEAD	159 A6	16	DW 20 B	587	1560	690	4545	TL	R-3	
23.1 - 26	DUAL BEAD HD	161 A6	18	DW 20 B	587	1560	690	4545	TT	R-3	
23.1 - 26	DUAL BEAD HD	161 A6	18	DW 20 B	587	1560	690	4545	TL	R-3	
23.1 - 26	HD DUAL BEAD SPECIAL	161 A6	18	DW 20 B	587	1560	690	4545	TL	R-3	
12.4 - 28		123 A6	8	W 11	325	1200	550	3576	TL	R-3	
16.9 - 28		135 A6	8	DW 15 L	440	1400	630	4074	TL	R-3	
16.9 - 30		137 A6	8	DW 15 L	440	1450	655	4220	TL	R-3	
18.4 - 30		139 A6	8	DW 16 L	475	1530	680	4395	TL	R-3	
18.4 - 30	HD	151 A6	14	DW 16 L	475	1530	680	4395	TT	R-3	
620/75 - 30		164 A6	18	DW 20 A ; DW 20 B	605	1675	0	0	TL	R-3	
24.5 - 32		164 A6	16	DH 21	625	1755	790	5226	TL		